

Model 603 pH/ORP Sensor

MODEL 603	BASIC DESCRIPTION (Municipal Submersion/Insertion pH Electrode)	
	Submersible/insertion combination pH sensor with general purpose 0 pH to 12 pH tip, coating immune solid polymer junction, includes Solution ground, Polypropylene body, 0 °C to 90 °C (32 °F to 194 °F), 3/4 inch MNPT mounting threads, lead length 1.5 m (5 ft) with tinned leads. Completely encapsulated for submersion or flow installations. Some analyzers may require industrial interface.	
ADD	ELECTRODE OPTIONS	
-4P	Platinum ORP tip	
ADD	TEMPERATURE COMPENSATION OPTIONS	
-32	100 ohm RTD	
-34	1000 ohm RTD. -34P, 1000 ohm RTD with pinjacks	
ADD	OPTIONS	
-71(x)	Short sensor cable, length less than 1.5 m (5 ft); specify (x) feet	
-72(x)	Long sensor cable, length greater than 1.5 m (5 ft), max length 30 m (100 ft); specify (x) feet, price per foot.	
-73	316 Stainless Steel Flowcell. P/N: A7200026	
-89	Stainless steel tag	
	RECOMMENDED CALIBRATION BUFFERS	
	Colored buffer 6-pack: 4, 7 & 10, P/N A1100054. For pure water see P/N A1100220-6P.	
	Buffer 4.0 pH, 500 mL bottle, red, P/N A1100051. For pure water see P/N A1100216.	
	Buffer 7.0 pH, 500 mL bottle, green, P/N A1100052. For pure water see P/N A1100217.	
	Buffer 10.0 pH, 500 mL bottle, blue, P/N A1100053. For pure water see P/N A1100218.	

Sample Order:

603	-34	pH electrode with 1000 ohm RTD
-----	-----	--------------------------------